Northern Silky Oak - Cardwellia sublimis

Wood Appearance

Colour – The heartwood is pink to brown in colour. Sapwood is usually almost white.

Grain - Moderately coarse textured and variable. Quarter sawn timber shows the decorative oak grain to best effect.

Wood Properties

Density - 560 kg/m³

Durability – Class 3 – Moderately resistance to decay when fully exposed to the weather, clear of the ground and well drained with free air circulation. Not recommended for in ground use.

Hardness – Soft (rated 5 on a 6 class scale) in relation to indentation and ease of working with hand tools.

Identification Features

Sapwood - Creamy white in colour

Heartwood - Pink to pinkish-brown in colour

Texture - Coarse and irregular, a broad ray figure on quarter sawn surfaces, grain straight

Wood Structure

Growth rings - Indistinct

Vessels – Large, numerous, solitary or in short tangential hoops between the rays. Tyloses absent, but occasionally vessels are filled with whitish deposits or deposits of red coloured gum.

Parenchyma – Abundant, aliform and confluent, including vessels between rays, forming loops, generally concave outwards; an occasional short tangential apotracheal band.

Rays – Of two distinct kinds (a) broad to very broad, plainly visible without a lens on all surfaces, and (b) fine, indistinct even under hand lens.

Other Features

Burning Splinter Test – A match size splinter burns to charcoal

MASTER WOODTURNING 37 LANCASTER STREET INGLEBURN NSW 2565 P: 02 9829 5000 F: 02 9829 5100 E: Sales@masterwoodturning.com.au

We do anything when it comes to wood